
MMBT3906T
PNP TRANSISTOR



1. BASE
2. EMITTER
3. COLLECTOR

FEATURES

for switching and amplifier applications

- Complementary to MMBT3904T
- Small Package

3N

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	-40	V
V_{CEO}	Collector-Emitter Voltage	-40	V
V_{EBO}	Emitter-Base Voltage	-5.0	V
I_C	Collector Current -Continuous	-200	mA
P_C	Collector Power Dissipation	150	mW
$R_{\Theta JA}$	Thermal Resistance, Junction to Ambient	833	℃/W
T_J	Operating Temperature	150	℃
T_{stg}	Storage Temperature	-55-150	℃

ELECTRICAL CHARACTERISTICS(Ta=25℃ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=-10μA,I_E=0	-40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=-1mA,I_B=0	-40			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=-10μA,I_C=0	-5			V
Collector cut-off current	I_{CBO}	V_{CB}=-30V,I_E=0			-0.1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=-5V,I_C=0			-0.1	μA
DC current gain	$h_{FE(1)}$	V_{CE}=-1V,I_C=-0.1mA	60			
	$h_{FE(2)}$	V_{CE}=-1V,I_C=-1mA	80			
	$h_{FE(3)}$	V_{CE}=-1V,I_C=-10mA	100		300	
	$h_{FE(4)}$	V_{CE}=-1V,I_C=-50mA	60			
	$h_{FE(5)}$	V_{CE}=-1V,I_C=-100mA	30			
Collector-emitter saturation voltage	$V_{CE(sat)1}$	I_C=-10mA,I_B=-1mA			-0.25	V
	$V_{CE(sat)2}$	I_C=-50mA,I_B=-5mA			-0.4	V
Base-emitter saturation voltage	$V_{BE(sat)1}$	I_C=-10mA,I_B=-1mA	-0.65		-0.85	V
	$V_{BE(sat)2}$	I_C=-50mA,I_B=-5mA			-0.95	V
Transition frequency	f_T	V_{CE}=-20V,I_C=-10mA,f=100MHz	250			MHz
Collector output capacitance	C_{obo}	V_{CB}=-5V,I_E=0,f=1MHz			4.5	pF
Input capacitance	C_{iob}	V_{EB}=-0.5V,I_E=0,f=1MHz			10	pF
Noise figure	NF	V_{CE}=-5V,I_c=0.1mA, f Ω			4	dB
Delay time	t_d	V_{CC}=-3V, $V_{BE(OFF)}$=-0.5V			35	ns
Rise time	t_r	I_C=-10mA , I_{B1}=-1mA			35	ns
Storage time	t_S	V_{CC}=-3V, I_C=-10mA			225	ns
Fall time	t_f	I_{B1}= I_{B2}=-1mA			75	ns

RATING AND CHARACTERISTIC CURVES




Fig.1 Grounded emitter output characteristics




Fig.2 Collector-emitter saturation voltage vs. collector current




Fig.3 DC current gain vs.collector current (I)




Fig.4 DC current gain vs. collector current (II)

RATING AND CHARACTERISTIC CURVES




Fig.8 Turn-on time vs. collector current




Fig.9 Rise time vs. collector current




Fig.10 Storage time vs. collector current




Fig.11 Fall time vs. collector current




Fig.6 Base-emitter saturation voltage vs. collector current





Fig.10 Power Dissipation vs Ambient Temperature

Soldering parameters


Reflow Condition		Pb-Free assembly (see as bellow)
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150℃
	-Temperature Max($T_{s(max)}$)	+200℃
	-Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquid us Temp (T_L) to peak)		3℃/sec. Max
$T_{s(max)}$ to T_L - Ramp-up Rate		3℃/sec. Max
Reflow	-Temperature(T_L)(Liquid us)	+217℃
	-Temperature(t_L)	60-150 secs.
Peak Temp (T_p)		+260(+0/-5)℃
Time within 5℃ of actual Peak Temp (t_p)		30 secs. Max
Ramp-down Rate		6℃/sec. Max
Time 25℃ to Peak Temp (T_P)		8 min. Max
Do not exceed		+260℃

FIG5: Reflow condition




Package Dimensions & Suggested Pad Layout

SOT-523



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.700	0.900	0.028	0.035
A1	0.000	0.100	0.000	0.004
A2	0.700	0.800	0.028	0.031
b1	0.150	0.250	0.006	0.010
b2	0.250	0.350	0.010	0.014
c	0.100	0.200	0.004	0.008
D	1.500	1.700	0.059	0.067
E	0.700	0.900	0.028	0.035
E1	1.450	1.750	0.057	0.069
e	0.500 TYP.		0.020 TYP.	
e1	0.900	1.100	0.035	0.043
L	0.400 REF.		0.016 REF.	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°


Dimensions in inches and (millimeters)



Dimensions	Value (in mm)
C	1.00
G	0.45
X	0.70
X1	1.40
X2	0.70
Y	0.60


Tape & rell specification

Tape



Symbol	Dimension (mm)
P0	4.00±0.20
P1	4.00±0.20
P2	2.00±0.20
D0	1.55±0.20
D1	0.65±0.20
E	1.55±0.25
F	3.60±0.20
W	8.00±0.20
A0	2.10±0.20
B0	2.20±0.20
K0	1.10±0.20
T	0.20±0.20

7” Reel



D2	177.0±5.0
D3	55Min.
D4	R24.6±2.0
G	R82.0±2.0
I	13.0±2.0
W1	10.20±3.0

Quantity: 3000PCS