
FEATURES

Excellent h_{FE} linearity and high h_{FE}

h_{FE} = 60 to 400 (V_{CE} = 2 V, I_C = 3 A)



1.Base
2.Collector
3.Emitter

■ **Simplified outline(SOT-89)**

D882

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Absolute Maximum Ratings (T_a = 25 °C)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	40	V
V_{CEO}	Collector-Emitter Voltage	30	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current -Continuous	3	A
P_C	Collector Power Dissipation	0.5	W
T_J	Junction Temperature	150	℃
T_{stg}	Storage Temperature	-55~150	℃


Characteristics at T_a = 25 °C


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C = 100μA, I_E=0	40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C = 10mA, I_B=0	30			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E= 100μA, I_C=0	6			V
Collector cut-off current	I_{CBO}	V_{CB}= 40V, I_E=0			1	μA
Collector cut-off current	I_{CEO}	V_{CE}= 30V, I_B=0			10	μA
Emitter cut-off current	I_{EBO}	V_{EB}= 6V, I_C=0			1	μA
DC current gain	$h_{FE(1)}$	V_{CE}=2V, I_C= 1A	60		400	
	$h_{FE(2)}$	V_{CE}=2V, I_C= 100mA	32			
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C= 2A, I_B= 0.2 A			0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C= 2A, I_B= 0.2 A			1.5	V
Transition frequency	f_T	V_{CE}= 5V , Ic=0.1A f =10MHz	50			MHz


CLASSIFICATION OF $h_{FE(1)}$


Rank	R	O	Y	GR
Range	60-120	100-200	160-320	200-400


RATING AND CHARACTERISTIC CURVES


















Soldering parameters


Reflow Condition		Pb-Free assembly (see as bellow)
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150℃
	-Temperature Max($T_{s(max)}$)	+200℃
	-Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquid us Temp (T_L) to peak)		3℃/sec. Max
$T_{s(max)}$ to T_L - Ramp-up Rate		3℃/sec. Max
Reflow	-Temperature(T_L)(Liquid us)	+217℃
	-Temperature(t_L)	60-150 secs.
Peak Temp (T_p)		+260(+0/-5)℃
Time within 5℃ of actual Peak Temp (t_p)		30 secs. Max
Ramp-down Rate		6℃/sec. Max
Time 25℃ to Peak Temp (T_P)		8 min. Max
Do not exceed		+260℃

FIG5: Reflow condition




Package Dimensions & Suggested Pad Layout


SOT89



Top View



Side View




Symbol		A	b	b1	C	D	D1	E	E1	e	e1	H	L
Dimensions (mm)	MIN	1.40	0.44	0.36	0.3	4.40	1.50	2.29	2.00†	1.50 BSC	3.00 BSC	3.94	0.89
	NOM	-	-	-	-	-	-	-	-			-	-
	MAX	1.60	0.56	0.48	0.5	4.60	1.75	2.60	2.29			4.25	1.20


Dimensions	Value (in mm)
C	2.50
G	3.60
X	1.40
X1	0.90
X2	0.90
Y	1.40
Y1	2.60
Y2	1.50
Y3	0.90

Tape & rell specification

Tape



13” Reel



Symbol	Dimension (mm)
P0	4.00±0.20
P1	8.00±0.20
P2	2.00±0.20
D0	1.60±0.20
D1	1.60±0.20
E	1.75±0.20
F	7.50±0.15
W	16.00±0.20
A0	6.30±0.20
B0	8.25±0.20
K0	2.60±0.20
T	0.23±0.10
D2	180.0±5.0
D3	60Min.
D4	R32.0±2.0
G	R86.5±2.0
H	R30.0±2.0
I	13.0±2.0
W1	13.20±2.0
W2	16.50±2.0
Quantity: 1000PCS	